



TOLERANCES UNLESS OTHERWISE SPECIFIED
未指定容許尺寸之公差

BASIC DIMENSIONS TOLERANCES	
UP TO 10 (10以下)	±0.1
ABOVE 10 TO 30 (10~30)	±0.3
ABOVE 30 TO 100 (30~100)	±0.5
ANGULAR DIMENSIONS(角度)	±5°
DIMENSION UNIT	mm

- SPECIFICATION**
- A: MATERIAL: NYLON 66
 - 1.BODY: NYLON 66
 - 2.TERMINAL: CU PLATED SN
 - 3.PIN: CU PLATED NI
 - B: CHARACTERISTICS:
 - 1.RATING: 2.5A 250V~(C-Ulus, ENEC & CCC & KC)
 - 2.INSULATION RESISTANCE:100MΩ MIN.AT 500VDC
 - 3.ELECTRIC STRENGTH : 3000 VAC/1MIN,LEAKAGE CURRENT UNDER 0.5mA
 - C: APPROVALS: C-Ulus, ENEC & CCC & KC
 - D: MATERIAL USED MUST BE COMPLY WITH HQI-0010
 - E: CAN MEET ROHS,ROHS2,0,HF

2			
1			
0	2012/08/15	新制訂	
NO	DATE	REVISION DESCRIPTION	REVISION DRAWN APPROVED

核准		Aatronjin		日期	20121105	投影法	第一角	機型	INLET SOCKET
校對		RZTang		日期	20121105	比例	1:1	料號	SK02
繪圖		WeiChen		日期	20121105	路徑	SK02\820068	料號	SK02-3401023221H
DRAWN BY		APPROVED		DATE	SCALE	DWG. NO	ITEM NO		

東莞市華之力電子有限公司 DONGGUAN HCR ELECTRONICS CO., LTD.